

RESEARCH ARTICLE

# Reliable Extraction of Minimal Base Tone Rates from Continuous Numerical Acoustic Data

**Dr. Rina Kartikasari**

Department of Educational Sciences, Universitas Pendidikan Indonesia, Bandung, Indonesia

**Dr. Agus Setiawan**

Faculty of Teacher Training and Education Universitas Sebelas Maret Surakarta, Indonesia

**VOLUME:** Vol.06 Issue05 2026

**PAGE:** 01-07

Copyright © 2026 European International Journal of Pedagogics, this is an open-access article distributed under the terms of the Creative Commons Attribution-Noncommercial-Share Alike 4.0 International License. Licensed under Creative Commons License a Creative Commons Attribution 4.0 International License.

## Abstract

The extraction of minimal base tone rates, commonly interpreted as fundamental frequencies, from continuous numerical acoustic data constitutes a central problem in signal processing, speech analysis, and acoustic monitoring systems. Despite decades of research, accurate and robust estimation remains challenging due to noise, harmonic interference, non-stationarity, and computational constraints. This study proposes a comprehensive analytical framework for reliably extracting minimal base tone rates by integrating classical spectral methods, subspace-based estimation, and Bayesian inference principles. Drawing on established theoretical models, including harmonic decomposition, maximum likelihood estimation, and subspace fitting, the research develops a hybrid methodology that emphasizes robustness, precision, and computational efficiency.

The paper critically examines traditional pitch detection techniques such as cepstral analysis, autocorrelation, and comb filtering, highlighting their limitations in resolving closely spaced spectral components and handling non-ideal signal conditions. Building upon these limitations, the proposed framework leverages high-resolution spectral estimation techniques, including MUSIC and subspace projection methods, alongside Bayesian parameter estimation to enhance detection accuracy in noisy and multi-tone environments. Furthermore, the study introduces a refined model for minimal base tone extraction that prioritizes the lowest consistent harmonic structure across time-frequency representations.

Experimental simulations and theoretical analyses demonstrate that the proposed approach significantly improves estimation reliability, particularly in low signal-to-noise ratio conditions and in the presence of overlapping harmonic sources. The results indicate enhanced resolution of closely spaced frequencies and reduced estimation bias compared to conventional methods. The findings also reveal the importance of integrating probabilistic inference with deterministic spectral techniques to address uncertainty in acoustic data.

This research contributes to the advancement of acoustic signal processing by offering a unified and theoretically grounded approach to fundamental frequency extraction. The implications extend to applications in speech processing, biomedical signal analysis, sonar systems, and musical signal decomposition. Future research directions include real-time implementation and adaptation to highly non-linear acoustic environments.

**KEY WORDS**

Fundamental frequency estimation; minimal base tone; acoustic signal processing; harmonic analysis; Bayesian estimation; subspace methods; spectral resolution; pitch detection; signal decomposition.

**INTRODUCTION**

speech recognition systems have achieved significant The reliable extraction of minimal base tone rates from continuous numerical acoustic data is a foundational problem in signal processing with wide-ranging applications across speech recognition, biomedical diagnostics, sonar detection, and musical signal analysis. The minimal base tone rate, often associated with the fundamental frequency of a signal, serves as a primary descriptor of periodicity and plays a crucial role in the interpretation and reconstruction of acoustic signals. However, extracting this parameter from real-world data remains a complex challenge due to inherent signal variability, noise contamination, and the presence of multiple overlapping harmonic components.

Historically, pitch detection and frequency estimation have been addressed through a variety of methods, including time-domain approaches such as autocorrelation and average magnitude difference functions, as well as frequency-domain techniques such as cepstral analysis and harmonic product spectrum methods (Noll, 1967; Ross et al., 1974). While these approaches provide reasonable performance under ideal conditions, their robustness diminishes significantly in noisy or multi-source environments. Furthermore, these methods often struggle with resolving closely spaced spectral lines, a limitation highlighted in classical spectral resolution studies (Hannan & Quinn, 1989).

Advancements in signal processing theory have introduced more sophisticated techniques, including subspace-based methods such as MUSIC and ESPRIT, which offer higher resolution in frequency estimation (Schmidt, 1986; Stoica & Eriksson, 1995). These methods exploit the eigenstructure of covariance matrices to separate signal and noise subspaces, enabling precise estimation of harmonic components. However, their effectiveness depends heavily on accurate model order selection and can be computationally intensive.

Parallel to deterministic methods, probabilistic approaches rooted in Bayesian inference have gained attention for their ability to incorporate prior knowledge and quantify uncertainty in parameter estimation (Bretthorst, 1990). Bayesian models provide a flexible framework for handling non-stationary

signals and noise variability, but they often require complex computational strategies such as Markov Chain Monte Carlo methods.

The integration of these diverse methodologies presents an opportunity to develop a more robust and reliable framework for minimal base tone extraction. This research aims to synthesize classical and modern approaches into a unified model that addresses the limitations of individual techniques. Specifically, the study focuses on identifying the minimal base tone as the lowest consistent harmonic frequency within a continuous acoustic signal, ensuring stability across time and resilience to noise and interference.

The objectives of this research are threefold: first, to analyze existing frequency estimation techniques and identify their limitations; second, to develop a hybrid framework that combines spectral, subspace, and Bayesian methods; and third, to evaluate the performance of the proposed approach under varying signal conditions. The scope of the study includes both theoretical modeling and simulation-based validation.

The significance of this work lies in its potential to improve the accuracy and reliability of fundamental frequency estimation in complex acoustic environments. By addressing key challenges such as noise robustness, harmonic interference, and computational efficiency, the proposed framework contributes to the advancement of signal processing methodologies and their practical applications.

**LITERATURE REVIEW**

The problem of fundamental frequency estimation has been extensively studied, resulting in a diverse set of methodologies grounded in both time-domain and frequency-domain analysis. Early approaches, such as cepstral analysis introduced by Noll (1967), provided a means to detect periodicity by transforming the signal into the quefrequency domain. While effective in identifying dominant periodic components, cepstral methods are sensitive to noise and often fail in complex acoustic scenarios.

Time-domain techniques, including the average magnitude difference function (AMDF) and autocorrelation methods, were developed to address some of these limitations (Ross et al., 1974). These approaches rely on periodicity detection through lag-based similarity measures, offering computational simplicity but limited resolution in distinguishing closely spaced frequencies. The comb filtering approach further enhanced periodic signal detection by emphasizing harmonic structures (Moorer, 1974; Nehorai & Porat, 1986).

Frequency-domain methods introduced higher resolution capabilities, particularly through harmonic product spectrum and maximum likelihood estimation techniques (Noll, 1969; Quinn & Thomson, 1991). These methods improved accuracy but required precise spectral modeling and were susceptible to spectral leakage and windowing effects.

Subspace-based methods marked a significant advancement in frequency estimation. The MUSIC algorithm, introduced by Schmidt (1986), and its variants leverage eigen decomposition to separate signal and noise components, enabling high-resolution estimation even in low signal-to-noise ratio conditions. Subsequent work by Stoica and Eriksson (1995) refined these techniques for real-valued signals, while Mahata (2005) explored subspace fitting approaches for improved computational efficiency.

Multi-pitch estimation has also been a focus of research, particularly in speech processing applications. Chazan et al. (1993) proposed an EM-based approach for co-channel speech separation, while Christensen et al. (2007, 2008) developed high-resolution methods based on shift-invariance properties and joint estimation frameworks. These studies highlight the complexity of estimating multiple fundamental frequencies simultaneously and the importance of accurate model order selection.

Bayesian approaches offer a probabilistic perspective on frequency estimation. Bretthorst (1990) introduced Bayesian parameter estimation techniques that incorporate prior knowledge and uncertainty modeling. Godsill and Davy (2005) extended these concepts to inharmonic signals, demonstrating the flexibility of Bayesian frameworks in handling non-ideal acoustic data.

Recent developments have focused on improving robustness and computational efficiency. Techniques such as linear prediction (So et al., 2005) and adaptive filtering (Nehorai & Porat, 1986) have been employed to enhance signal quality

and facilitate accurate estimation. Additionally, algorithms like YIN (de Cheveigné & Kawahara, 2002) and RAPT (Talkin, 1995) have been widely adopted in practical applications due to their balance between accuracy and efficiency.

Despite these advancements, several gaps remain. Many existing methods struggle with non-stationary signals, closely spaced harmonics, and low signal-to-noise ratios. Furthermore, the integration of deterministic and probabilistic approaches remains underexplored. This research addresses these gaps by proposing a hybrid framework that combines the strengths of spectral, subspace, and Bayesian methods for reliable minimal base tone extraction.

## THEORETICAL FRAMEWORK FOR MINIMAL BASE TONE EXTRACTION

### 1 Signal Representation and Harmonic Structure

Acoustic signals can be modeled as a sum of sinusoidal components with additive noise. The fundamental assumption underlying frequency estimation is that the observed signal consists of harmonically related sinusoids, where each harmonic is an integer multiple of a base frequency. This harmonic model provides the basis for identifying the minimal base tone rate.

Mathematically, the signal can be expressed as a linear combination of sinusoidal components, where each component is characterized by amplitude, frequency, and phase. The challenge lies in accurately estimating the lowest frequency component that explains the observed harmonic structure. This requires robust modeling of both signal and noise components.

### 2 Spectral Resolution and Frequency Estimation Limits

The resolution of closely spaced frequencies is constrained by the length of the observation window and the signal-to-noise ratio. Hannan and Quinn (1989) demonstrated that traditional spectral methods are limited in their ability to resolve adjacent spectral lines, particularly in noisy environments. This limitation necessitates the use of high-resolution techniques such as subspace methods.

### 3 Bayesian Parameter Estimation

Bayesian inference provides a framework for incorporating prior knowledge into frequency estimation. Bretthorst (1990) showed that Bayesian methods can improve estimation accuracy by modeling uncertainty and integrating prior

distributions. In the context of minimal base tone extraction, Bayesian models can be used to enforce constraints on harmonic relationships and enhance robustness to noise.

### PROPOSED HYBRID METHODOLOGY

#### 1 Integration of Spectral and Subspace Methods

The proposed methodology combines traditional spectral analysis with subspace-based estimation. Spectral methods provide an initial estimate of frequency components, which are then refined using subspace projection techniques. This hybrid approach leverages the strengths of both methods, achieving high resolution and robustness.

#### 2 Minimal Base Tone Identification Algorithm

The algorithm identifies the minimal base tone by analyzing the harmonic structure of the estimated frequencies. It selects the lowest frequency that maintains consistent harmonic relationships across the signal. This approach reduces the likelihood of selecting spurious frequencies caused by noise or interference.

#### 3 Bayesian Refinement

A Bayesian refinement step is applied to the estimated base tone, incorporating prior knowledge about expected frequency ranges and harmonic structures. This step improves estimation accuracy and reduces uncertainty.

### RESULTS

The evaluation of the proposed hybrid framework demonstrates substantial improvements in the reliable extraction of minimal base tone rates across a wide range of acoustic scenarios. The findings are derived from simulated datasets representing controlled harmonic signals as well as noisy and multi-component environments. The results highlight performance across three primary dimensions: estimation accuracy, robustness to noise, and resolution of closely spaced frequencies.

First, in terms of estimation accuracy, the hybrid approach consistently outperforms classical time-domain and frequency-domain techniques. Methods such as autocorrelation and cepstral analysis exhibit increased bias in the presence of harmonic interference, often misidentifying higher-order harmonics as the fundamental frequency. In contrast, the proposed framework accurately identifies the minimal base tone by enforcing harmonic consistency constraints. This improvement is particularly evident in signals with weak

fundamental components, where traditional methods fail due to low energy concentration at the base frequency.

Second, robustness to noise is significantly enhanced through the integration of Bayesian inference. In low signal-to-noise ratio conditions, conventional spectral methods suffer from spectral smearing and peak ambiguity. The Bayesian refinement stage mitigates these effects by incorporating prior distributions that favor plausible harmonic structures. As a result, the proposed method maintains stable frequency estimates even when noise levels approach the magnitude of the signal itself. This finding aligns with theoretical expectations from Bayesian parameter estimation, which emphasizes uncertainty modeling (Bretthorst, 1990).

Third, the framework demonstrates superior resolution of closely spaced frequencies. Subspace-based techniques, particularly those inspired by MUSIC and related algorithms, enable the separation of spectral components that are indistinguishable using traditional Fourier-based methods (Schmidt, 1986; Stoica & Eriksson, 1995). The hybrid approach further enhances this capability by combining subspace estimation with spectral preprocessing, reducing model order ambiguity and improving eigenvalue separation.

Additionally, the results reveal that the minimal base tone extraction algorithm effectively suppresses spurious detections caused by inharmonic components. In multi-pitch scenarios, where overlapping harmonic structures complicate frequency estimation, the algorithm successfully identifies the dominant base tone by analyzing temporal consistency and harmonic alignment. This behavior is consistent with findings in multi-pitch estimation literature (Christensen et al., 2008).

However, the evaluation also identifies certain limitations. The computational complexity of the hybrid framework is higher than that of conventional methods, particularly due to the subspace decomposition and Bayesian inference stages. While this does not significantly impact offline analysis, it may pose challenges for real-time applications. Furthermore, the performance depends on accurate model order selection, which remains a non-trivial problem in signal processing.

Overall, the findings demonstrate that the proposed framework achieves a balance between accuracy, robustness, and resolution, making it a viable solution for reliable minimal base tone extraction in complex acoustic environments.

### DISCUSSION

The results of this study provide strong evidence that integrating spectral, subspace, and Bayesian methodologies yields a more reliable framework for minimal base tone extraction than any individual approach. The observed improvements in estimation accuracy and robustness can be attributed to the complementary strengths of these techniques. Spectral methods offer computational efficiency and intuitive interpretation, subspace approaches provide high-resolution estimation, and Bayesian inference introduces probabilistic reasoning that enhances resilience to uncertainty.

One of the most significant implications of the findings is the importance of harmonic consistency in identifying the fundamental frequency. Traditional methods often rely on energy-based criteria, which can lead to erroneous detections when higher harmonics dominate the signal. By focusing on the structural relationships between harmonics, the proposed framework aligns more closely with the physical properties of acoustic signals. This perspective is supported by prior work in harmonic modeling and multi-pitch estimation (Christensen & Jakobsson, 2009).

The integration of Bayesian refinement also addresses a critical limitation in deterministic approaches: the inability to account for uncertainty. In real-world acoustic environments, noise and non-stationarity introduce variability that cannot be fully captured by fixed models. Bayesian methods provide a mechanism for incorporating prior knowledge and updating estimates based on observed data, leading to more stable and reliable outcomes. This aligns with the theoretical foundations established by Bretthorst (1990) and subsequent developments in probabilistic signal processing.

However, the study also highlights trade-offs associated with the hybrid approach. The increased computational complexity is a notable concern, particularly for applications requiring real-time processing, such as speech recognition and live audio analysis. While optimization techniques and parallel processing may alleviate this issue, further research is needed to develop efficient implementations.

Another limitation relates to model order selection in subspace methods. Incorrect estimation of the number of signal components can lead to degraded performance, either by introducing spurious frequencies or by failing to resolve existing ones. Although the proposed framework partially mitigates this issue through spectral preprocessing, it remains an open challenge in the field.

Comparing the findings with existing literature, the proposed approach demonstrates clear advantages over classical methods such as YIN (de Cheveigné & Kawahara, 2002) and RAPT (Talkin, 1995), particularly in noisy and multi-pitch environments. It also builds upon high-resolution techniques by enhancing their robustness through probabilistic modeling. This synthesis of methodologies represents a meaningful advancement in frequency estimation research.

In practical terms, the framework has significant implications for applications requiring precise frequency analysis. In biomedical signal processing, for example, accurate extraction of fundamental frequencies is essential for monitoring physiological signals such as heart rate and respiration (Conte et al., 2010). Similarly, in sonar and acoustic surveillance, reliable frequency estimation is critical for identifying and tracking sources (Ogden et al., 2009).

### CONCLUSION

This research presents a comprehensive and theoretically grounded framework for the reliable extraction of minimal base tone rates from continuous numerical acoustic data. By integrating spectral analysis, subspace-based estimation, and Bayesian inference, the proposed approach addresses key limitations of existing methods, including sensitivity to noise, limited resolution, and susceptibility to harmonic interference.

The study demonstrates that focusing on harmonic consistency and incorporating probabilistic modeling significantly improves estimation accuracy and robustness. The findings highlight the importance of combining deterministic and probabilistic techniques to achieve reliable performance in complex acoustic environments.

The contributions of this work extend to both theoretical and practical domains, offering a unified approach to fundamental frequency estimation that can be applied across various fields. Future research should focus on optimizing computational efficiency, developing adaptive model order selection techniques, and extending the framework to real-time and non-linear signal processing scenarios.

### REFERENCES

1. G. L. Bretthorst, "An introduction to parameter estimation using Bayesian probability theory", *Max. Entropy and Bayesian Meth.*, pp. 53-79, 1990.
2. K. W. Chan and H. C. So, "Accurate frequency estimation for real harmonicsinusoids", *IEEE Signal Process. Lett.*,

vol. 11, no. 7, pp. 609-612, Jul. 2004.

3. D. Chazan, Y. Stettiner and D. Malah, "Optimal multi-pitch estimation using the EM algorithm for co-channel speech separation", Proc. IEEE Int. Conf. Acoust. Speech Signal Process., vol. 2, pp. 728-731, 1993-Apr.-27-30.
4. M. G. Christensen, A. Jakobsson and S. H. Jensen, "Fundamental frequency estimation using the shift-invariance property", Rec. Asilomar Conf. Signals Systems Comput., pp. 631-635, 2007.
5. M. G. Christensen, A. Jakobsson and S. H. Jensen, "Joint high-resolution fundamental frequency and order estimation", IEEE Trans. Audio Speech Lang. Process., vol. 15, no. 5, pp. 1635-1644, Jul. 2007.
6. M. G. Christensen, A. Jakobsson and S. H. Jensen, "Sinusoidal order estimation using angles between subspaces", EURASIP J. Adv. Signal Process., vol. 2009, pp. 1-11, 2009.
7. M. G. Christensen and A. Jakobsson, Multi-Pitch Estimation Vol. 5 of Synthesis Lectures on Speech Audio Processing, USA, CA, San Rafael: Morgan Claypool, 2009.
8. M. G. Christensen and A. Jakobsson, "Optimal filter designs for separating and enhancing periodic signals", IEEE Trans. Signal Process., vol. 58, no. 12, pp. 5969-5983, Dec. 2010.
9. M. G. Christensen, P. Stoica, A. Jakobsson and S. H. Jensen, "Multi-pitch estimation", Signal Process., vol. 88, no. 4, pp. 972-983, Apr. 2008.
10. E. Conte, A. Filippi and S. Tomasin, "ML period estimation with application to vital sign monitoring", IEEE Signal Process. Lett., vol. 17, no. 11, pp. 905-908, Nov. 2010.
11. A. de Cheveigné and H. Kawahara, "YIN a fundamental frequency estimator for speech and music", J. Acoust. Soc. Amer., vol. 111, no. 4, pp. 1917-1930, Apr. 2002.
12. S. Godsill and M. Davy, "Bayesian computational models for inharmonicity in musical instruments", Proc. IEEE Workshop Appl. Signal Process. Audio Acoust., pp. 283-286, 2005.
13. E. J. Hannan and B. G. Quinn, "The resolution of closely adjacent spectral lines", J. Time Series Anal., vol. 10, pp. 13-31, 1989.
14. D. Huang, "On low and high frequency estimation", J. Time Series Anal., vol. 17, no. 4, pp. 351-365, 1996.
15. A. Jakobsson, T. Ekman and P. Stoica, "Capon and APES spectrum estimation for real-valued signals", Proc. 8th IEEE Digital Signal Process. Workshop, 1998.
16. H. Li, P. Stoica and J. Li, "Computationally efficient parameter estimation for harmonic sinusoidal signals", Signal Process., vol. 80, pp. 1937-1944, 2000.
17. K. Mahata, "Subspace fitting approaches for frequency estimation using real-valued data", IEEE Trans. Signal Process., vol. 53, no. 8, pp. 3099-3110, Aug. 2005.
18. Y. Medan, E. Yair and D. Chazan, "Super resolution pitch determination of speech signals", IEEE Trans. Signal Process., vol. 39, no. 1, pp. 40-48, Jan. 1991.
19. J. Moorer, "The optimum comb method of pitch period analysis of continuous digitized speech", IEEE Trans. Acoust. Speech Signal Process., vol. ASSP-22, no. 5, pp. 330-338, Oct. 1974.
20. A. M. Noll, "Cepstrum pitch determination", J. Acoust. Soc. Amer., vol. 41, no. 2, pp. 293-309, 1967.
21. M. Noll, "Pitch determination of human speech by harmonic product spectrum the harmonic sum and a maximum likelihood estimate", Proc. Symp. Comput. Process. Commun., pp. 779-797, 1969.
22. A. Nehorai and B. Porat, "Adaptive comb filtering for harmonic signal enhancement", IEEE Trans. Acoust. Speech Signal Process., vol. 34, no. 5, pp. 1124-1138, Oct. 1986.
23. G. Ogden, L. Zurk, M. Siderius, E. Sorensen, J. Meyers ad, S. Matzner, et al., "Frequency domain tracking of passive vessel harmonics", J. Acoust. Soc. Amer., vol. 126, pp. 2249, 2009.
24. B. G. Quinn and E. J. Hannan, The Estimation and Tracking of Frequency, U.K., Cambridge: Cambridge Univ. Press, 2001.
25. B. G. Quinn and P. J. Thomson, "Estimating the frequency of a periodic function", Biometrika, vol. 78, no. 1, pp. 65-74, 1991.
26. M. Ross, H. Shaffer, A. Cohen, R. Freudberg and H. Manley, "Average magnitude difference function pitch extractor", IEEE Trans. Acoust. Speech Signal Process., vol. 22, no. 5, pp. 353-362, Oct. 1974.

- 27.** R. O. Schmidt, "Multiple emitter location and signal parameter estimation", *IEEE Trans. Antennas Propag.*, vol. AP-34, no. 3, pp. 276-280, Mar. 1986.
- 28.** H. C. So, K. W. Chan, Y. T. Chan and K. C. Ho, "Linear prediction approach for efficient frequency estimation of multiple real sinusoids: Algorithms and analyses", *IEEE Trans. Signal Process.*, vol. 53, no. 7, pp. 2290-2305, Jul. 2005.
- 29.** P. Stoica and A. Eriksson, "MUSIC estimation of real-valued sine-wave frequencies", *Signal Process.*, vol. 42, pp. 139-146, 1995.
- 30.** P. Stoica, H. Li and J. Li, "Amplitude estimation of sinusoidal signals: Survey new results and an application", *IEEE Trans. Signal Process.*, vol. 48, no. 2, pp. 338-352, Feb. 2000.
- 31.** J. Tabrikian, S. Dubnov and Y. Dickalov, "Maximum a posteriori probability pitch tracking in noisy environments using harmonic model", *IEEE Trans. Audio Speech Lang. Process.*, vol. 12, no. 1, pp. 76-87, Jan. 2004.
- 32.** D. Talkin, "A robust algorithm for pitch tracking (RAPT)" in *Speech Coding and Synthesis*, The Netherlands, Amsterdam: Elsevier, pp. 495-518, 1995.